

MyPBX - Embedded Hybrid IP-PBX for Small Businesses

MyPBX SOHO is a standalone embedded hybrid PBX for small businesses and remote branch offices of larger organizations. MyPBX also offers a hybrid solution (a combination of VoIP applications using legacy telecom equipment) alternative for enterprises who are not yet ready to migrate to a complete VoIP solution.



Specifications

Users: 32

Concurrent Calls (Max): 8

Voicemail: 4000min

Interface: Up to 4 Analog Ports (**FXO/FXS**)
Up to 4 **BRI** Ports

Flash: 512 MB Onboard Flash

RAM: 64 MB Onboard RAM

LAN: 1 (10/100Mbps)

Protocol: SIP (RFC3261)

Transport: UDP, TCP, TLS, SRTP

DTMF: RFC2833, SIP INFO, In-band

Codec: G.711 A/u-law, G.722, G.726, G.729 A, GSM, Speex, ADPCM, H261, H263, H263p, H264, MPEG4.

LED: **Red** for FXO, **Green** for FXS, **Orange** for BRI.

Network: DHCP Server, VLAN, DDNS.

Size: 193x153x30mm

Weight: 500g

Power Supply: AC 100~240V/50~60Hz (DC 12V, 1A)

Environment Conditions

Operation Range: 0°to 40°C, 32° to 122° F

Storage Range: -20° to 65°C, 4° to 149° F

Humidity: 10-90% non-condensing

Features

Automated Attendant (IVR)

Auto Provision

Blind Transfer

Blacklist

Call Detail Records (CDR)

Call Forward

Call Parking

Call Pickup

Call Routing

Call Transfer

Call Waiting

Call Recording

Caller ID

Conference

Direct Inward System Access (DISA)

Distinctive Ringtone

Do Not Disturb (DND)

Firewall

Follow me

Intercom/Zone Intercom

Music on Hold

Music on Transfer

PIN User (PIN Code Control)

Queue

Ring Group

Route by Caller ID

Skype Integration (Skype Connect)

Speed Dial

Three-way Calling

Voicemail

[END]