

"Норком" ЕООД
 тел: 0878272160; 0878272225
 тел/факс: 02 9733165

e-mail: office@norcom-it.com
 e-mail: norcom@abv.bg

RIELLO UPS устройства

Парт. Номер	Описание	Мощност VA/W	Размери, WxDxH mm
-------------	----------	--------------	-------------------

UPS Riello серия - iDialog (IDG)

VFD - USB порт и софтуер за Windows/Linux/Mac

AIDG4001RU	IDG 400	400VA/240W	90 x 232 x 192
AIDG6001RU	IDG 600	600VA/360W	90 x 232 x 192
AIDG8001RU	IDG 800	800VA/480W	90 x 232 x 192
AIDG1K21RU	IDG 1200	1200VA/720W	93 x 310 x 270
AIDG1K61RU	IDG 1600	1600VA/960W	93 x 310 x 270



UPS Riello серия iPlug (IPG)

VFD - USB port и софтуер за Windows/Linux/Mac*

AIPG600DRU	IPG 600 DE	600VA/360W	185 x 313 x 99
AIPG800DRU	IPG 800 DE	800VA/480W	185 x 313 x 99
AIPG600IRU	IPG 600 IT	600VA/360W	185 x 313 x 99
AIPG800IRU	IPG 800 IT	800VA/480W	185 x 313 x 99
AIPG600FRU	IPG 600 FR	600VA/360W	185 x 313 x 99
AIPG800FRU	IPG 800 FR	800VA/480W	185 x 313 x 99
AIPG600ERU	IPG 600 UK	600VA/360W	185 x 313 x 99
AIPG800ERU	IPG 800 UK	800VA/480W	185 x 313 x 99



Line-Interactive UPS Riello Series Net Power (NPW)

VI - AVR, USB порт и софтуер, съвместим с Windows /Linux/Mac (downloadable)

ANPW600AA3	NPW 600	600VA/360W	100 x 287 x 142
ANPW600DA3	NPW 600 DE (Shuko socket)	600VA/360W	100 x 287 x 142
ANPW800AA5	NPW 800	800VA/480W	100 x 287 x 142
ANPW800DA5	NPW 800 DE (Shuko socket)	800VA/480W	100 x 287 x 142
ANPW1K0AA3	NPW 1000	1000VA/600W	146 x 350 x 160
ANPW1K5AA5	NPW 1500	1500VA/900W	146 x 397 x 205
ANPW2K0AA5	NPW 2000	2000VA/1200W	146 x 397 x 205

Line-Interactive UPS Riello Series Net Dialog (NDG)

VI - AVR, RS 232 порт и софтуер, съвместим с Windows /Linux/Mac (downloadable)

ANDG8001RU	NDG 800	800VA/480W	140 x 375 x 180
ANDG1K01RU	NDG 1000	1000VA/600W	140 x 375 x 180
ANDG1K51RU	NDG 1500	1500VA/900W	140 x 375 x 180
ANDG2K01RU	NDG 2000	2000VA/1200W	140 x 410 x 214



Парт. Номер	Описание	Мощност VA/W	Размери, WxDxH mm
-------------	----------	--------------	-------------------

Line-Interactive UPS Riello Series Vision (VST)

VI sine wave - AVR - RS 232/USB - софтуер съвместим с Windows /Linux/Mac (downloadable)

BVST8001RU	VST 800	800VA/640W	120 X 443 X 247
BVST1K11RU	VST 1100	1100VA/880W	120 X 443 X 247
BVST1K51RU	VST 1500	1500VA/1200W	120 X 443 X 247
BVST2K01RU	VST 2000	2000VA/1600W	120 X 443 X 247



Line-Interactive UPS Riello Series Vision Dual (VSD)

Line interactive - sine wave - tower/rackmount - RS 232/USB - софтуер, съвместим с Windows /Linux/Mac

BVSD1K1AA3	VSD 1100	1100VA/990W	87(2U)x425x450(19")
BVSD1K5AA5	VSD 1500	1500VA/1350W	87(2U)x425x450(19")
BVSD2K2AA3	VSD 2200	2200VA/1980W	87(2U)x625x450(19")
	VSD 2200 + BB SDH 72-A3 VSD	2200VA/1980W	17 min 29 min 58 min
	2200 + BB SDH 72-M1 VSD	2200VA/1980W	
	2200 + 2 x BB SDH 72-M1	2200VA/1980W	
BVSD3K0AA5	VSD 3000	3000VA/2700W	87(2U)x625x450(19")



Line-Interactive UPS Riello Series Dialog Vision Rack (DVR)

Line interactive - sine wave - микропроцесор - AVR - RS 232/USB - софтуер съвместим с Windows /Linux/Mac

BDVR5001RU	DVR 500	500VA/350W	438(19")x460x44,3(IU)
BDVR8001RU	DVR 800	800VA/540W	438(19")x460x44,3(IU)
BDVR1K11RU	DVR 1100	1100VA/740W	438(19")x460x44,3(IU)



Line-Interactive UPS Riello Series Vision Dual ER (VSD)

Long back-up version - no internal batteries / 8A battery charger (compatible with battery capacity above 40Ah only)

BVSD2K2LNB	VSD 2200 ER	2200VA/1760W	87(2U) x 625 x 450(19")
	VSD 2200 ER + BB SEP 72-B1	2200VA/1760W	73 min
BVSD3K0LNB	VSD 3000 ER	3000VA/2400W	87(2U) x 625 x 450(19")
	VSD 3000 ER + BB SEP 72-B1	3000VA/2400W	53 min



On line double conversion UPS Riello Series Sentinel Pro (SEP)

On line double conversion (VFI) - USB/RS232 - софтуер, съвместим с Windows /Linux/Mac (downloadable)

CSEP7001RU	SEP 700	700VA/560W	158 x 400 x 235
CSEP1K01RU	SEP 1000	1000VA/800W	158 x 400 x 235
CSEP1K51RU	SEP 1500	1500VA/1200W	158 x 422 x 235
CSEP2K21RU	SEP 2200	1500VA/1200W	10 min @ 1500VA
CSEP2K21RU	SEP 2200	2200VA/1760W	190 x 446 x 333
CSEP3K01RU	SEP 3000	3000VA/2400W	190 x 446 x 333



Парт. Номер	Описание	Мощность VA/W	Размеры, WxDxH mm
-------------	----------	---------------	-------------------

On line double conversion UPS Riello Series Sentinel Pro ER

Long back-up version - no internal batteries / 8A battery charger (compatible with battery capacity)

CSEP1K0LRU	SEP 1000 ER	1000VA/800W	158 x 422 x 235
	SEP 1000 ER + BB SEP 36-B1	1000VA/800W	80 min
CSEP2K2LRU	SEP 2200 ER	2200VA/1760W	190 x 446 x 333
	SEP 2200 ER + BB SEP 72-B1	2200VA/1760W	67 min
CSEP3K0LRU	SEP 3000 ER	3000VA/2400W	190 x 446 x 333



Battery extensions for SEP-VSD ER series

JSEP036PA3	BB SEP36-A3 (suitable for SEP 1000)	3/12V 7Ah	158 x 422 x 235
JSEP036PM1	BB SEP 36-M1 (suitable for SEP 1000)	3x2/12V 12Ah	158 x 422 x 235
JSEP036PB1	BB SEP 36-B1 (suitable for SEP 1000)	3/12V 40Ah	215 x 655 x 630
JSEP072PA3	BB SEP72-A3 suitable for SEP 2200/3000	6/12V 7Ah	190 x 446 x 333
JSEP072PM1	BB SEP72-M1 suitable for SEP2200/3000	6x2/12V 7Ah	190 x 446 x 333
JSEP072PB1	BB SEP 72-B1 suitable for SEP2200/3000	6/12V 40Ah	215 x 655 x 630

On line double conversion UPS Riello Series Sentinel Dual (SDH)

On line double conversion - microprocessor control - USB/RS 232 - software compatible with

CSDH1K01RU	SDH 1000	1000VA/900W	87(2U) x 425 x 450(19")
CSDH1K51RU	SDH 1500	1500VA/1350W	87(2U) x 425 x 450(19")
CSDH2K21RU	SDH 2200	2200VA/1980W	87(2U) x 425 x 450(19")
CSDH3K01RU	SDH 3000	3000VA/2700W	87(2U) x 425 x 450(19")



On line double conversion UPS Riello Series Sentinel Dual ER

Long back-up version - no internal batteries / 8A battery charger (compatible with battery capacity)

CSDH2K2LRU	SDH 2200 ER	2200VA/1760W	87(2U) x 625 x 450(19")
	SDH 2200 ER + BB SEP 72-B1	2200VA/1760W	67 min
CSDH3K0LRU	SDH 3000 ER	3000VA/2400W	87(2U) x 625 x 450(19")
	SDH 3000 ER + BB SEP 72-B1	3000VA/2400W	35 min
	SDH 3000 ER + 2xBB SEP 72-B1	3000VA/2400W	95 min



Battery extensions for SDH-VSD series

JSDH036PA3	BB SDH 36-A3 (suitable for SDH 1000)	3/12V 7Ah	87(2U) x 425 x 450(19")
JSDH036PM1	BB SDH 36-M1 (suitable for SDH 1000)	6/12V 7Ah	87(2U) x 425 x 450(19")
JSEP036PB1	BB SDH 36-B1** (suitable for SDH 1000)	3/12V 40Ah	215 x 655 x 630
JSDH072PA3	BB SDH 72-A3(suitable for SDH220/300)	4/12V 7Ah	87(2U) x 625 x 450(19")
JSDH072PM1	BB SDH 72-M1(suitable for SDH220/300)	8/12V 7Ah	87(2U) x 625 x 450(19")
JSEP072PB1	BB SEP 72-B1**(suitable for SDH220/300)	8/12V 12Ah	215 x 655 x 630

** Tower version only

Парт. Номер	Описание	Мощност VA/W	Размери, WxDxH mm
-------------	----------	--------------	-------------------

On line double conversion UPS Riello Series Sentinel Dual (SDL)

On line double conversion - tower/rackmount - RS 232/USB - software compatible with Windows

CSDL3K3AA4	SDL 3300 7 min/full load	3300VA/2300W	175(411) x 455(19") x 520
	SDL 3300 + BB SDL 108-A4 3300 + BC SDL 108-M1	3300VA/2300W 3300VA/2300W	19 min 30 min
	SDL 3300 + BC SDL 108-M8	3300VA/2300W	45 min
	SDL 3300 + BC SDL 108-B1	3300VA/2300W	80 min
CSDL4K0AA4	SDL 4000 56 min/full load SDL 4000 + BB SDL 108-A4	4000VA/2400W 4000VA/2400W	175(411) x 455(19") x 520 15 min
	SDL 4000 + BC SDL 108-M1	4000VA/2400W	27 min
	SDL 4000 + BC SDL 108-M8	4000VA/2400W	43 min
	SDL 4000 + BC SDL 108-B1	4000VA/2400W	75 min
CSDL5K0AA4	SDL 5000 9 min/full load	5000VA/3500W	175(411) x 455(19") x 660
	SDL 5000 + BB SDL 192-A3	5000VA/3500W	22 min
	SDL 5000 + BC SDL 192-A6	5000VA/3500W	33 min
	SDL 5000 + 2xBC SDL 192-A6	5000VA/3500W	58 min
CSDL6K0AA4	SDL 6000 7 min/full load	6000VA/4200W	175(411) x 455(19") x 660
	SDL 6000 + BB SDL 192-A3	6000VA/4200W	18 min
	SDL 6000 + BC SDL 192-A6	6000VA/4200W	27 min
	SDL 6000 + 2xBC SDL 192-A6	6000VA/4200W	48 min



Гаранция: За всички UPS системи - 2 (две) години

За повече информация:

"Норком" ЕООД

тел: 0878272160; 0878272225

тел/факс: 02 9733165

e-mail: office@norcom-it.com

e-mail: norcom@abv.bg